



Berulub PV DAB 10

Pharmaceutical Vaseline in DAB 10 - quality

3000201

Rev.05_14.12.2012

Description
<p>Berulub PV DAB 10 is a mixture of micro crystalline waxes of highly refined petroleum fractions.</p> <p>Berulub PV DAB 10 is suitable for pharmaceutical applications.</p>

Application
<p>To protect surfaces from corrosion and as lubricant in case there are only minor requirements to aging resistance, pressure absorption, temperature and relubrication intervals.</p> <p>Berulub PV DAB 10 can be applied manually by brush or in melted condition, whereby the part can also be wetted by dipping.</p>

Properties

- **Service temperature**
-20 °C to +45 °C
- **Neutral in smell**
- **Physiologically harmless**
- **Suitable for pharmaceutical applications**
- **Complies with the regulations of the „Deutschen Arzneimittelbuches“ (DAB 10)**
- **NSF-H1**



Nonfood Compounds
Program Listed H1
141991

- **Halal certificate**



Density at 70 °C	g/cm ³	approx. 0,83	DIN 51 757
Penetration	1/10 mm	165 - 185	DIN 51 580
Kin. viscosity at 100 °C	mm ² /s	approx. 9	DIN 51 562
Solidification point	°C	50 - 55	DIN ISO 2207

Characteristic data

- **Appearance: Light coloured, pasty consistency**

Storage: **Berulub PV DAB 10** has to be protected against heat, water, dust and light and must be stored in closed rooms.

The above data correspond to latest technology, modifications reserved. This information is intended as a guide and does not necessarily represent a marketing specification. In individual cases tests have to be carried out by the consumer. Further data upon request.