

PRODUCT SPECIFICATION

Valpar Industrial Ltd.
13 Balloo Drive
Bangor, Co.Down
N.Ireland, BT19 7QY

PRODUCT CODE	PVC6.3X11.5BRAID		
ISSUE No.	5	DATE OF ISSUE	10/11/14

PRODUCT DESCRIPTION	6.3MM BORE CLEAR FLEXIBLE REINFORCED PVC TUBE
----------------------------	---

MAIN APPLICATION	FOR USE IN THE DISPENSE OF BEVERAGES
-------------------------	--------------------------------------

MATERIALS

INNER LAYER	SOFT CLEAR LOW TOXICITY PVC
BRAID	TERYLENE YARN LAPPING (2 X 8),PITCH 32mm ± 1mm
OUTER LAYER	SOFT CLEAR LOW TOXICITY PVC
FOOD COMPLIANCE	The material is approved for food contact use by the F&DA regulations

DIMENSIONS / TOLERANCE

OVERALL DIAMETER	11.5mm +0.25mm -0.25mm	WALL THICKNESSES	Total	2.6mm +0.25mm -0.25mm
INTERNAL DIAMETER	6.3mm +0.25mm -0.25mm			

PROPERTIES

OPERATING TEMPERATURE	MIN	-10°C	MAX	+55°C	*Not suitable for outdoor use
SAFE WORKING PRESSURE @ 20 °C	12 bar				
SAFE OPERATING LIMIT @ 20 °C	13.2 bar				

NB: At pressures above 4 bar the hose, although perfectly fit for purpose, is likely to shrink lengthwise - as much as 10% at 6 bar. It is therefore important that allowances are made for this shrinkage on any installation.

PRINT LEGEND

MANUFACTURER - SIZE - TRACEABILITY CODE
Tubing is printed in black at maximum intervals of 250mm

PACKAGING

STANDARD COIL LENGTH	30 metres (± 1m)	Supplied on pallets or in boxes depending on quantity. Tolerance on length: +/- 0.5 metre.
-----------------------------	------------------	---

© Valpar Industrial Limited
Valpar Industrial Ltd proprietary and confidential information. All design rights or other intellectual property rights in this document and the copyright in this document are the property of Valpar Industrial Limited. Any unauthorised use thereof will constitute an infringement of the intellectual property rights of Valpar Industrial Limited.